

A002 : SELSTAT

high solids antistatic metallised polish

Description of product

High performance dissipative floor polish. Retains performance even at humidities as low as 11% Independently tested to IEC 61340 - 4 - 1 and BS 7506. Makes charge dissipate off a standard vinyl floor. Improves the conductivity of conductive flooring. Applies, hardens and protects like a normal floor polish. Non-slip

Product Uses

For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring.

Directions

Selstat must be applied to a clean grease free floor. Strip old polish with Selate then rinse thoroughly with clean water, allow floor to dry. Apply a thin even film of Selstat using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 minutes). COVERAGE: 60 square metres per litre. Full independent test reports are available on our website. N.B. Buffing is not recommended as this will reduce the static dissipative property of the polsh.

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



typical dilution
neat

iNsight recommended product uses

Flooring - applying floor polish (mop application)

Product Hazards and PPE Requirements

Contains : Benzisothiazolinone

Risk Phrases

Contains Benzisothiazolinone May produce an allergic reaction.

Safety Phrases

Technical Data

Composition	A blend of acrylic copolymers, resins and copolymer wax incorporating a antistat agent, wetting agents and film forming aids in a stable water based emulsion form incorporating metal cross linking additives.
Appearance	Opaque liquid
Colour	white
Viscosity	<10 cps
Density	1.028
pH	8.0 - 8.2
Activity	18%
Fragrance	Characteristic, slightly sweet
Stability	2 years in unopened containers
Storage	Protect from freezing

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industryleading standards.
 - Selden minimises wastage, packaging and transportation.
 - If it can be recycled, it will be recycled.
 - Our chemicals policy exceeds regulatory requirements.
 - We don't expect other people to clean up after us.
 - Conserving energy, preserving resources.
 - By being innovative, we strive to do better.
 - We like to work in partnership with our clients.
- Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer

Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



ISO 9001



ISO 14001



ISO 18001

UKAS
accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

