

SAFETY DATA SHEET

Page 1 of 7
Issued: 12/05/2021; Revision No.2
GB Regulation S.I. 2020 No. 1577

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product Identifier

Material name : Q-Bright

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Stainless Steel Cleaner.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Quattro Hygiene Group
136-140 Old Shoreham Road
Brighton
East Sussex
BN3 7RD

Tel. : 03335 673010

Fax. :

Email (for SDSs) : info@quattrohygiene.co.uk

1.4 Emergency tel. no.: 03335 673010 (Office hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to GB Classification, Labelling and Packaging of Substances and Mixtures Regulation (CLP):

Physical and Chemical Hazards	Aerosol Cat.1; H222; H229
Human health	Not classified
Environment	Not classified

2.2 Label elements

Labelling according to GB CLP:

Signal word: Danger



Pictogram(s):

Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
Precautionary statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
	P261	Avoid breathing vapour/spray.
	P280	Wear protective gloves.
	P271	Use only outdoors or in a well-ventilated area.
	P501	Dispose of in accordance with local/national regulations.

SAFETY DATA SHEET

Page 2 of 7
Issued: 12/05/2021; Revision No.2
GB Regulation S.I. 2020 No. 1577

2.3 Other hazards In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures:

Hazardous components

Chemical Name	CAS No./ EC No./ Index No./ Reg. No	Classification (CLP)	Content
DISTILLATES (PETROLEUM) HYDROTREATED LIGHT (ODOURLESS KEROSENE)	64742-47-8 265-149-8 649-422-00-2 01-2119484819-18-xxxx	Asp. Tox. 1, H304	50-70%
LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene)	68476-85-7 270-704-2 -	Flam.Gas 1, H220 Gas under pressure, H280	10-30%

Substance classifications are taken from the GB Mandatory Classification and Labelling (MCL) list, or if absent, from supplier's information.

See Section 16 for the full text of the H-statements noted above.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice: Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

Inhalation: Remove to fresh air. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed: May cause irritation to skin and eyes with prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed: See skin and eye contact information above.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide; dry chemical powder; alcohol or polymer foam.

Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Irritating/toxic fumes may be released at elevated temperatures.

5.3 Advice for fire-fighters:

Special protective equipment: Wear self-contained breathing apparatus. Use personal protective equipment.

Further information: Standard procedure for chemical fires. Use water spray to cool containers.
Do not allow fire run-off to enter drains.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

6.2 Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

6.4 References to other sections

See sections 8 and 13 for personal protection and disposal information.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Do not breathe spray mist. Avoid contact with skin and eyes. Handle with care.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Keep away from food, drink and animal feed.

7.3 Specific end use(s): No information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 Control parameters**

Chemical name	8hr TWA	15min STEL	Reference
Liquefied petroleum gas	1750 mg/m ³ /1000ppm	2810 mg/m ³ /1250 ppm	EH40/2005

DNEL/PNEC: No data available.

8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Personal protective equipment

Respiratory protection: Unlikely to be necessary in normal circumstances; if vapour levels are high, wear a respirator conforming to EN 140 with type A filter or better.

11. TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****Acute toxicity**

Chemical name	Oral (LD50)	Inhalation (LC50)	Dermal (LD50)
Distillates (Petroleum), Hydrotreated Light	>5000 mg/kg (Rat)	>5 mg/l (Rat) 4h	>2000 mg/kg (Rabbit)
Liquefied petroleum gas	Not applicable	>20mg/l (Rat) 4h	Not applicable

Skin corrosion/irritation:	Not classified as a skin irritant, but prolonged contact may result in skin irritation.
Serious eye damage/eye irritation:	Not classified as an eye irritant.
Respiratory or skin sensitisation:	Not classified as a respiratory or skin sensitizer.
Repeated dose toxicity:	Not classified for repeated dose toxicity.
Carcinogenicity:	Not classified as a carcinogen.
Mutagenicity:	Not classified as a mutagen.
Toxicity for reproduction:	Not classified as toxic for reproduction.
Specific target organ toxicity (STOT): Single exposure	Not classified for STOT SE, but high levels of vapour may cause central nervous depression, headache, dizziness, nausea.
Specific target organ toxicity (STOT): Repeated exposure	Not classified for STOT RE.
Further information	The product as a whole may cause irritation of skin and upper respiratory tract if exposed to high levels of spray mist.

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

Chemical name	Species	Test	Value
Distillates (Petroleum), Hydrotreated Light	Daphnia	EC50 48h	1-10 mg/l
	Fish	LL50 96h	1-10 mg/l
	Algae	EC50 72h	1-10 mg/l

Physical properties indicate that petroleum gases will rapidly volatilise from the aquatic environment and that acute and chronic effects would not be observed in practice.


12.2 Persistence and degradability	Liquefied petroleum gas is expected to be readily biodegradable. Oxidises rapidly by photochemical reactions in air. The solvent content is expected to be inherently biodegradable.
12.3 Bioaccumulative potential	Contains constituents expected to bioaccumulate.
12.4 Mobility in soil	The liquid content is insoluble in water and will float on the surface.
12.5 Results of PBT and vPvB assessment	Contains no PBT or vPvB substances.
12.6 Other adverse effects	None expected.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**


Disposal operations: Dispose of in accordance with local and national regulations.
Contact licensed waste disposal company. Most aerosols can be recycled.
Do not pierce or burn or use a cutting torch on the empty aerosol container.

14. TRANSPORT INFORMATION

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:



The following information relates to all other aerosols not transported as Limited Quantities:

14.1 UN number	ADR/RID/ADN; IMDG; ICAO	1950
14.2 UN proper shipping name	AEROSOLS	
14.3 Transport hazard class(es)	ADR/RID/ADN Class	2, 5F
	ADR/RID/ADN Class	Class 2, Gases
	ADR Label No.	2.1
	IMDG Class	2
	ICAO Class/Division	2
	ICAO Subsidiary risk	2.1
		
	Transport labels	
14.4 Packing Group	ADR/RID/ADN; IMDG; ICAO	Not applicable for aerosols
14.5 Environment hazards	Marine Pollutant	Not applicable for aerosols.
14.6 Special precautions for user	EMS	F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		Not applicable for aerosols.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

GB MCL (Mandatory Classification and Labelling).

Statutory Instruments

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

S.I. 2020 No 1577: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Guidance Notes

Health and Safety Executive Workplace Exposure Limits EH40.

15.2 Chemical Safety Assessment

Chemical Safety Assessments/Reports (CSA/CSR) are not required for mixtures.

16. OTHER INFORMATION

This safety data sheet is prepared in accordance with the requirements of the UK REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation - The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020. (S.I. 2020 No. 1577).

Reason for revision: Updated “Distillates (petroleum), hydrotreated light” classification, resulting in change to product classification; references to GB CLP added.

Full text of H-statements referred to under sections 2 and 3

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.

Abbreviations and acronyms

CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.

STOT: Single Target Organ Toxicity (Section 2; 11).

SE: Single exposure (Section 2)

TWA: Time-weighted average. (Section 8).

STEL: Short-term exposure limit. (Section 8).

PBT: Persistent, Bioaccumulative, Toxic. (Section 12).

vPvB: very Persistent and very Bioaccumulative. (Section 12).

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]